

Vidyo Infrastructure

High-quality, secure video conferencing and collaboration platform

Business Challenge

Video technology has rapidly become an essential part of workplace culture and customer engagement. IT professionals need an affordable, flexible, and secure infrastructure platform that allows them to quickly and efficiently bring video to their organization without breaking the bank.

Transform your enterprise with a secure and reliable HD-quality video platform

Solution Overview


For organizations that want video collaboration capabilities but require those solutions to be implemented in their data centers, Vidyo's on-premises infrastructure provides an advanced and cost-effective video conferencing platform. From hardware appliances to software running in virtualized server environments, Vidyo's infrastructure delivers enterprise-grade video quality, healthcare-grade privacy, and industry-leading reliability.

Vidyo is powered by patented video routing core technology that delivers unparalleled quality in multiparty meetings, unmatched reliability over mobile, and no-hassle workflows for guests. Vidyo delivers the ideal platform for video-based healthcare, financial services, enterprise collaboration, customer engagement, and apps needing embedded video communication.

IT Benefits

- **Easily scalable**
Easily scale to your organization with availability in both standard and XL capacities as a physical server appliance or as a virtual appliance for VMware ESXi.
- **Meet enterprise and healthcare security standards**
Leverage TLS, SRTP, H.235, and AES 128-bit encryption with healthcare-grade privacy.
- **Support interoperability**
Third-party H.323 and SIP-based systems provide investment protection.
- **Count on superior performance**
Dynamic adaptation technology over the internet and Wi-Fi means fewer dropped calls and support tickets.


Vidyo Infrastructure Components



VidyoPortal

The VidyoPortal provides centralized administration, call signalling, authentication, directory services, and policy management.


- **Flexible configuration and management** of endpoints, infrastructure, software, and licenses
- **Automatic user provisioning** via LDAP/Active Directory, SAML, or web services API
- **Multi-tenant option** that allows you to serve up to 1,000 private-label tenants from a single infrastructure



VidyoRouter

The heart of any Vidyo deployment, the VidyoRouter is a Selective Forwarding Unit (SFU) for handling real-time media for all calls while providing firewall traversal, dynamic bandwidth adaptation, and multiparty calls.

- **Outstanding quality** that supports native rate and resolution matching per endpoint, up to 4K resolution
- **Multipoint content support** that allows multiple participants to share content at the same time
- **Extremely efficient for large-scale deployments** with low cost of ownership and a small physical footprint



VidyoGateway

The VidyoGateway provides an interface for H.323 and SIP-based systems to interact with the Vidyo platform, enabling integrations into existing real-time media infrastructure.

- **Enhanced capacity and resiliency** with clustering and high availability deployment options
- **Centralized web-based interface** to simplify administration, configuration, and maintenance
- **Support for content sharing and flexible layouts**, including gallery view, continuous presence, and active speaker



Vidyo Server for WebRTC

The Vidyo Server for WebRTC makes it possible for users to join a Vidyo conference using a WebRTC-enabled web browser, thus eliminating the need to download any software.

- **Dynamically scalable capacity** based on provisioned resources with support for server clustering
- **Click-to-connect** capability for frictionless HD-quality video meetings
- **Multiparty** video and content sharing



VidyoReplay

VidyoReplay brings streaming and recording capability to video conferences, extending both the reach to any viewer and the time available to a viewer with on-demand playback.

- **Recording and webcasting** with optional PIN protection to secure live and recorded content
- **Export and edit** videos in standard MP4 format and integrate with third-party content management systems (CMS) and content delivery networks (CDN)
- **Browser-based player and library** with easy access from any device, including mobile

Application Specifications

Security (all products): FIPS 140-2 compliant (cryptography kernel only), TLS, SRTP, HTTPS, SSL, AES

VidyoRouter	Capacity: 100 concurrent HD connections, or 150 concurrent HD connections (VidyoRouter XL)
VidyoPortal	Capacity: Up to 10,000 users and 100 tenants, or expand with VidyoPortal XL for more than 10,000 users and 1,000 tenants
VidyoGateway	<p>Protocols and Standards: Video: H.264 SVC (UCIF mode 2s), H.264 AVC, H.263 Audio: G.711, G.722, Opus; Signaling: H.323 and SIP Data Sharing: H.239, BFCP; Encryption: SRTP, H.235 AES, and TLS Far-End Camera Control: H.224; Dialing: E.164, URI (H.323 Annex O and SIP URI) Firewall/NAT Traversal: RFCs 7362, 3581, and 5626</p> <p>Content Sharing: Up to 1080p30</p> <p>Layouts: Gallery view, continuous presence, active speaker</p>
VidyoReplay	<p>Recording Capacity: 6 HD/1080p concurrent recording sessions 12 HD/720p concurrent recording sessions 24 SD concurrent recording sessions 30 CIF concurrent recording sessions 50 audio-only concurrent recording sessions</p> <p>Streaming Protocol: HLS streaming (mobile), HTTP/FLV streaming (PC)</p> <p>Export Format: MP4, H.264, AAC</p> <p>Streaming Storage: Up to 300 concurrent viewers, 2,500 hours stored HD content at 1Mbps, 1,560 hours stored HD content at 1.6Mbps (default), 40 hours stored HD content at 1.6Mbps (Capacity figures are approximate and vary based on content type. More storage capacity possible using network-attached storage.)</p>
Vidyo Server for WebRTC	<p>WebRTC Video Codec: VP8, VP9, H.264 video codecs across Chrome, Firefox, and Edge browsers</p> <p>High Availability: Hot standby 1+1 support</p>

Virtual Edition Requirements

Hypervisor: VMWare ESXi 5.5 or higher

Host Server: Intel-based servers with a Xeon CPU at 2.2GHz or faster, supporting Intel Sandy Bridge (or newer) architecture, with AES-NI and hyperthreading enabled, 1Gbps NIC

Product	Resource Allocation / Resource Reservation	Capacity
VidyoPortal™ VE	Allocation: Minimum 2GHz CPU, 8GB RAM, 50GB Reservation: 8GHz, 8GB RAM	Up to 10,000 users Tenants: 1,000
VidyoRouter™ VE 100	Allocation: 8 vCPU, 8GB vRAM, 100GB vDisk Reservation: 18GHz CPU, 6GB RAM	100 concurrent HD connections
VidyoRouter™ VE 25	Allocation: 4 vCPU, 4GB vRAM, 100GB vDisk Reservation: 6GHz CPU, 4GB RAM	25 concurrent HD connections

Product	Allocation	Concurrent Connections				
		1080p	720p	SD	CIF	Audio
VidyoGateway™ VE	2GHz, 2GB RAM	N/A	1	2	4	10
	4.4GHz, 2GB RAM	1	2	4	8	20
	8.8GHz, 6GB RAM	2	4	9	15	50
	12GHz, 8GB RAM	3	5	12	25	75
	20GHz, 12GB RAM	4	8	18	50	100
	25GHz, 15GB RAM	5	10	20	50	125

Product	Allocation	Concurrent Connections				
VidyoReplay™ VE	19GHz, 8GB RAM	1080p	720p	SD	CIF	Audio
	9.5GHz, 4GB RAM	4	8	16	30	50
Vidyo Server for WebRTC	2GHz, 2GB RAM	1080p	720p	SD	CIF	Audio
		1	4	5	6	9

* Displayed specs are for a cluster node only.

** Virtual machine specs provided for general guidance. Please review the [VM provisioning requirements section of the administration guide](#) for the appropriate product for specific configuration.

Hardware Specifications

Server	VidyoRouter, VidyoPortal, VidyoGateway	VidyoRouter XL, VidyoPortal XL, VidyoGateway XL, VidyoReplay
Physical Dimensions (without ear and bezel)	Height: 1.67" (42.6 mm) Width: 15.5" (393.7 mm) Depth: 17.1" (431 mm) Weight: 17.76 lbs (8.058 kg) Form Factor: 1U rack mount (ReadyRails™ static rails included)	Height: 1.69" (42.8 mm) Width: 17.09" (434.0 mm) Depth: 25.28" (642.3.1 mm) Weight: 43.87 lbs (19.9 kg) Form Factor: 1U rack mount (ReadyRails™ sliding rails included)
Power Supply	Input: 100-240v ~, 4-2A, 50-60Hz Output: 250W Non-Redundant (auto-ranging) Consumption: 69W (idle), 86W (full load) Dissipation: 112 BTU (idle), 300 BTU (full load)	Input: 100-240v ~, 3.5A, 50-60Hz Output: 2x 550W Redundant (auto-ranging, platinum efficiency) Consumption: 112W (idle), 210W (full load) Dissipation: 245 BTU (idle), 645 BTU (full load)
Regulatory Compliance	Safety: EN 60950-1:2006, A11:2009/IEC 60950-1:2005 ed2 EMC: EN 55022:2006 +A1:2007/CISPR 22:2005 +A1:2005 +A2:2006 EN 55024:1998 +A1:2001 +A2:2003/CISPR 24:1997 +A1:2001 +A2:2002 EN 61000-3-2:2006 +A1:2009 +A2:2009/IEC 61000-3-2:2005 +A1:2008 +A2:2009 EN 61000-3-3:2008/IEC 61000-3-3:2008 Australia C-TICK Class A; Argentina IRAM; Canada NRTL ICES Class A; China CCC Class A; Croatia KONCAR Class A; European Union CE Class A; Germany TUV IECIE IECIE CB; Israel SII Class A; Japan VCCI Class A; Mexico NOM; Moldova INSM Class A; Nigeria SONCAP; Norway NEMKO Class A; Russia GOST Class A; South Africa NRCS SABS Class A; South Korea KC Class A; Taiwan BSMI Class A; United States NRTL FCC Class A; Vietnam ICT Class A	Safety: EN 60950-1:2006/IEC 60950-1:2005 ed2 EMC: EN 55022:2006 +A1:2007/CISPR 22:2005 +A1:2005 EN 55024:1998 +A1:2001 +A2:2003/CISPR 24:1997 (modified) +A1:2001 +A2:2002 EN 61000-3-2:2006/IEC 61000-3-2:2005 (Class D) EN 61000-3-3:1995 +A1:2001 +A2:2005/IEC 61000-3-3:1994 +A1:2001 +A2:2005 Australia C-TICK Class A; Argentina IRAM; Canada NRTL ICES Class A; China CCC Class A; Croatia KONCAR Class A; European Union CE Class A; Germany TUV IECIE IECIE CB; Israel SII Class A; Japan VCCI Class A; Mexico NOM; Moldova INSM Class A; Nigeria SONCAP; Norway NEMKO Class A; Russia GOST Class A; South Africa NRCS SABS Class A; South Korea KC Class A; Taiwan BSMI Class A; United States NRTL FCC Class A; Vietnam ICT Class A
Network	x RJ45 LAN ports - 100BASE-TX and 1000BASE-T	
Environment	Operating Temperature Range: (for altitude ≤ 900 m or 2952.75 ft): 10°C to 35°C (50°F to 95°F) Non-Operating Temperature Range: -40°C to 65°C (-40°F to 149°F) Operating Humidity Range: 10% to 90% (non-condensing) Non-Operating Humidity Range: 5% to 95%	



Vidyo, Inc. (Corporate Headquarters)
 433 Hackensack Ave., Hackensack, NJ 07601, USA
 Tel: 201.289.8597 Toll-free: 866.998.4396
 Email: vidyoinfo@vidyo.com

EMEA
 emea@vidyo.com
 +33 (0) 488 718 823

APAC
 apac@vidyo.com
 +852 3478 3870

INDIA
 india@vidyo.com
 +91 124 4111671

© Vidyo, Inc. All rights reserved. Vidyo and other trademarks used herein are trademarks or registered trademarks of Vidyo, Inc. or their respective owners. All specifications subject to change without notice, system specifics may vary. Vidyo products are covered by one or more issued and/or pending US or foreign patents or patent applications. Visit www.vidyo.com/patent-notice for information.